

# CMX40

## Heavy Duty Coin Sorter

With proven coin detection, a speed of up to 2,300 coins per minute, automatic feeding and a large hopper capacity CMX40 offers more than any other machines in it's class. CMX40 is suitable for medium and small cash centers but also affordable for other location which have to handle a lot of coins.



## FAST AND DURABLE

CMX40 is simple to operate and most functions are available with just one push of a button. The large belt-driven hopper feeds up to 6,500 coins and once and processes them with a speed of up to 2,300 coins per minute.

- Counting and sorting speed Up to 2,300 coins per minute with full detection
- Hopper capacity of 3,800 coins (Standard Euro-Mix) and 6,500 coins max.
- Automatic belt-driven feeding
- Big and robust rubber keys
- Low maintenance

## SAFETY AND COMFORT

The non-volatile memory secures your counting data also in case of power failure. The integrated thermal printer provides receipts for your deposits and further information for accounting. The successful certification and the optionally available statistic box allow credit institutions to work and report according the regulations for cash professionals.

- Contact-less cashMAX® detection system with 4 detection parameters
- Non-volatile memory: count, total and bag contents individually for 8 cashiers
- Printed thermal printer build-in
- Big coin size range: D: 14 - 34 mm T: 0.8 – 3.5 mm
- 2 bag stops levels, 1 - 9,999 coins per bag
- Optional statistic box
- Complies with EU regulation 1210/2010



CMX40 with optional stand and bag holders

## FACTS AND SPECS

### Product versions

- CMX40 (23304)

### Included accessories

Coin boxes, cleaning set, power cable, user manual, 1 bag holder

### Options

- Bagging unit (2220A0001)
- Paper rolls for printer (22307)
- External display L (22309+22310)
- External display S (22318+22310)
- Tubing set (EUR/21003)
- RS232 cable (22308)
- Open reject box (ZJY504-Z001)
- Statistic module (22310)
- Machine stand (23301)

### Interfaces

- RS232, display

### Dimensions and weight

- 820 mm (W), 360 mm (D), 455 mm (H)
- 58 KG

### Technical Specifications

- 230 VAC (+5%/-15%), 50/60Hz, 230W
- 10° C to 35° C, 20% to 80% RH
- Acoustic noise level LpA < 80 dB(A) (uncertainty: 2) LpA Standb < 43 dB(A)
- CE, RoHS compliant